

FT5000



A high-volume, reliable through-the-wall ATM you can afford.

For years, the ATM industry has trusted Triton for innovative technology that's practical and cost-efficient, and Triton delivers again with the FT5000, a versatile through-the-wall ATM that offers high performance for a surprisingly low investment.

Our long-time experience in producing innovative, high quality cash dispensing machines has led us to develop this product focused on the financial institution market.

What makes the Triton FT5000 most popular with banks and credit unions is its highly cost-efficient operation. Financial

institutions can place a drive-up or a walk-up configuration with two to four cassettes based on transaction volumes. You can count on the reliable operation that has made Triton a leader in the industry.

Performance. Reliability. Easy and inexpensive to service. Thanks to Triton, there's finally a through-the-wall unit made just for you.



FT5000

In Detail



A high-volume, reliable through-the-wall ATM you can afford.

FEATURES:

- Two to four cassettes
- 80 mm thermal printer with presenter
- 2 MB journal storage (32,768 records)
- 10.4" (264 mm) VGA color display with 640 x 480 resolution, optional sun light viewable
- Rear service panel with 5.7" (145 mm) touch screen monochrome display with 320 x 240 resolution
- Dip-style card reader; optional dip EMV smart card reader, optional EMV motorized card reader (Track 1,2,3 Read), or EMV motorized card reader/encoder (Track 1,2,3 Read, Track 3 Write)
- Americans with Disabilities Act (ADA) compliant
- Audio transactions for the visually impaired
- Encrypting PIN Pad (EPP) to comply with all international encryption standards, PCI compliant, optional metal EPP
- Triton Connect™ compatible
- UL 291 Business Hours cabinet or optional UL 291 Level 1 Safe
- Electronic lock or optional Kaba Mas Cencon lock
- Multilingual capabilities
- Dial-up 56k baud internationally certified modem and TCP/IP communications standard
- Dimensions:
 - Depth (Island): 34.0" (864 mm)
 - Depth (Standard): 39.0" (991 mm) for walls as thick as 10.0" (254 mm)
 - Width: Vault 16.9" (429 mm); Sleeve 21.3" (541 mm)
 - Height: 62.6" (1590 mm)
 - Weight: up to 868 lb (394 kg) weight varies with options
- Advertising revenue potential:
 - Decals and signage
 - Couponing
 - Display graphics

TECHNICAL SPECS:

- RISC microprocessor
- Microsoft Windows® CE 5.0
- 128 MB flash memory, expandable
- 128 MB RAM
- One compact FLASH socket
- Five serial ports


OPERATING SPECS:

- Temperature:
 - Vault/Electronics: 50° to 104° F (10° to 40° C)
 - External: -30° to 122° F (-35° to 50° C)
- Relative humidity:
 - 20% to 80% non-condensing
- Power consumption:
 - 2.0 A @ 115 VAC at 60 Hz
 - 1.0 A @ 230 VAC at 50 Hz

Triton Headquarters • 522 East Railroad Street
Long Beach, Mississippi 39560 USA
With offices throughout the U.S. and worldwide including Canada, UK, Australia, and Hong Kong
Phone: 1-228-868-1317 • Toll free: USA & Canada 1-800-367-7191
www.triton.com • Email: sales@triton.com

© 2008 Delaware Capital Formation, Inc. All Rights Reserved. TRITON, TRITON WHERE MONEY COMES FROM, DOVER and DOVER logo are registered trademarks of Delaware Capital Formation, Inc., a wholly-owned subsidiary of Dover Corporation.

Current as of 2/08 · FT5000 product sheet-07203-00035



The dimensions shown comply with U.S. Federal ADA guidelines. For installation within the U.S., be sure to check state and local guidelines for complete compliance. For non-USA installations, check regulations for the country in which the machine will be installed.

**specifications subject to change without notice*

ATM INSTALLATION SPACE REQUIREMENTS FOR ADA COMPLIANCE